



MULTI BLOCK T

A FLEXIBLE
SOLUTION FOR
YOUR SITE



Applicable for loaders and
articulated dump trucks



Designed and Developed by Bridgestone

BRIDGESTONE **Firestone**

Tire Features

Sidewall and tread

Excellent cut resistance avoiding unexpected damage and subsequent downtime



Tie bars

Limit lug flex and movement for long, even wear

Non-directional pattern design

Easy to install and good even wear tendency



Open shoulder design

Contributes to traction



Size	TRA Code/ Application	Star Rating	Type	Recommended Rim/ Flange Height	Approximate Inflated Dimensions (mm)				OTD (mm)
					OD	OW	SLR	SLW	
175R25	E3/L3	**/*	T/L	14.00/1.5	1351	443	603	513	29
205R25	E3/L3	**/*	T/L	17.00/2.0	1482	536	652	620	32
235R25	E3/L3	**/*	T/L	19.50/2.5	1601	615	698	700	34
265R25	E3/L3	**/*	T/L	22.00/3.0	1735	688	751	793	38
295R25	E3/L3	**/*	T/L	25.00/3.5	1867	766	806	882	42

T/L: Tubeless, OD: Overall Diameter, OW: Overall Width, SLR: Static Loaded Radius, SLW: Static Loaded Width, OTD: Original Tread Depth

USE OF THIS PRODUCT OTHER THAN FOR INTENDED PURPOSES IS STRICTLY PROHIBITED

BRIDGESTONE Firestone